

Compresor cu filet

BELLOWS EXPANSION JOINTS

Mod fabricare:

Metale inelare ondulate, formate si tuburi longitudinale sudate. Proiectate si fabricate in conformitate cu standardele "EJMA" respectand standardele de presiune si temperatura din DIN 2401.

Materiale:

Filetele si mansoanele interne sunt fabricate din otel pur conform cu DIN 17440. Conexiunile finale fie din otel pur fie din otel carbonat.

Conexiuni:

Masoane fixe sau mobile.

Diametre:

DN 25(1")-DN 2600(104")

Presiune:

Pana la 64 de bari, depinde de diametru si temperatura operationala.

Temperatura:

-196°C pana la 600°C depinde de material

Aplicabilitate:

In toate tipurile de tevi la miscare mecanice. Pentru mai multe detalii vs rugam sa ne contactati.

Construction:

Annularly corrugated metal bellows formed from longitudinal welded tubes. Designed and manufactured fully in accordance with the respective "EJMA" standards and in conformity with the pressure and temperature ratings as per DIN 2401.

Materials:

Bellows and internal sleeves (liners) made of stainless steel according to DIN 17440 bright. End connections either stainless steel or carbon steel. Other materials on request.

Connections:

Fixed or floating flanges, welding ends.

Nominal diameters:

DN 25 (1") - DN 2600 (104")

Pressure ratings:

Up to max. 64 bar operation pressure depending on nominal diameter and operation temperature.

Temperature ranges:

- 196°C up to + 600°C depending on the material.

Operation applications:

Compensation of thermal and mechanical movements in pipelines of all kinds. Please consult us for advise on applications, specifications and installation.



Compresor axial

AXIAL EXPANSION JOINTS

Singurele compresoare axiale prezentate aici sunt modelele "Ex stock" care sunt disponibile cu manse mobile sau fixe, de asemenea si cu incheieturi sudate conform cu DIN . Acestea pot fi livrate in scurt timp.

Alte standade (ANSI,BS,JIS)la cerere.

Presiune: PN 16.

Proiectate si fabricate pentru a inlocui cel putin 1000 de cicluri la o anumita presiune si miscare

Single axial expansion joints in this leaflet are "Ex stock" units, which are available with floating or fixed flanges, as well as welding ends according to DIN with short delivery times.

Other standards (ANSI,BS,JIS) on request.

Pressure rating: PN 16

Designed and manufactured to compensate at least 1.000 full cycles at rated pressure and movements.

Please state in your order sheet:

"Ex stock" single axial expansion joint and: nominal diameter (DN), pressure rating (PN), materials, connections, medium and operation temperature as well as details of applications.

Lateral, universal, angular, hinge, x-press, pressure balanced-types and rectangular expansion joints are available on request as well as designed and manufactured according to customers requirements.

Compressoare cu extensie axiale cu masoane mobile

DN	d	∅		L ₃₀	L ₆₀	b	Surub	Aria efectiva cm ²
25	38	115	85	110	—	16	4	16
32	42.4	140	100	115	—	16	4	18
40	48.3	150	110	120	—	16	4	23
50	60.3	165	125	110	—	18	4	37
65	76.1	185	145	110	195	18	4	58
80	88.9	200	160	110	190	20	8	79
100	114.3	220	180	115	200	20	8	128
125	139.7	250	210	120	210	22	8	183
150	168.3	285	240	140	225	22	8	268
200	219.1	340	295	140	245	24	12	437
250	273	405	355	140	235	26	12	705
300	323.9	460	410	140	235	28	12	984

Compressoare axiale cu capete sudate

AXIAL EXPANSION JOINTS WITH WELDING ENDS

DN	d	Aria efectiva Effective area cm ²	L ₃₀	L ₆₀
25	38	16	210	—
32	42.4	18	215	—
40	48.3	23	220	—
50	60.3	37	210	—
65	76.1	58	210	295
80	88.9	79	210	290
100	114.3	128	215	300
125	139.7	183	220	310
150	168.3	268	240	325
200	219.1	437	240	345
250	273	705	240	335
300	323.9	984	250	340

L₃₀ : lungimea de extensie de 30 mm.

L₆₀ : lungimea de extensie de 60 mm

Dimensiunea in mm.

L₃₀ : Overall length for 30 mm. rated movements.

L₆₀ : Overall length for 60 mm. rated movements.

Dimensions in mm.

